

## WARNING SIGNS WS

### Polyester film, Halogen free, on sheet

□ Consist of **WS** symbols supplemented by information in text form **WST**, or text only signs which can be used in combination with symbol only signs.

Available in different graphic modes and formats, for marking equipment, machinery and installations in a detailed and efficient way.

**Material:** Polyester film over-laminated with transparent film resistant to UV, thickness approximately 0,1 mm. Resistant to Water, Oil, Grease, Alcohol, Detergent, Alkaline Substances and Atmospheric Agents.

Low flammability, self extinguishing. Recommended for application to equipment for internal or external use, but not directly exposed to atmospheric agents.

If exposed to atmospheric agents, the life of the label may be limited to five years.

### Certificates

□ 2011/65/EU

## WARNING SIGNS WS

### Technical characteristics

Material	Polyester film
Halogen Free	yes
Adhesive	yes
Min operating temperature range	-40 °C
Max operating temperature range	130 °C
Colour	Yellow RAL 1003

□

# WARNING SIGNS WS

## List of products

### WS-AD

Meaning of the symbol Generic hazard

Geometric shape triangular

Type	Printed text	Length	Height	Quantity per sheet	Pack qty
200000				64	320
200000-BULK		12.5 mm		323	1,615
200001		25 mm		24	240
200001-BULK		25 mm		120	1,200
200002		50 mm		10	50
200002-BULK		50 mm		30	900
200003		100 mm		2	10
200003-BULK		100 mm		6	300
200004		150 mm		2	10
200005		200 mm		1	5
200006		300 mm		1	1
2557AD017-GB	PERICOLO! Dispositivi meccanici in movimento	210 mm	105 mm	1	3
0400AD035	PERICOLO	50 mm		5	25
2653AD035	ATTENZIONE! PERICOLO	74 mm	37 mm	3	15
2655AD035	ATTENZIONE! PERICOLO	131 mm	65 mm	1	10

### WS-HT

Meaning of the symbol Electrical hazard

Geometric shape triangular

Type	Height	Length	Quantity per sheet	Pack qty	Printed text
0400HT012-BULK	50 mm	15	750	230 V	
200100	12.5 mm	64	320		
200100-BULK	12.5 mm	323	1,615		
200101	25 mm	24	240		
200101-BULK	25 mm	120	1,200		
200102	50 mm	10	50		
200102-BULK	50 mm	30	900		
200103	100 mm	2	10		
200103-BULK	100 mm	6	450		
200105	200 mm	1	5		
200106	300 mm	1	1		
0401HT008	100 mm	1	10	110 V	
0401HT012	100 mm	1	10	230 V	
0402HT012	150 mm	1	5	230 V	
0400HT012	50 mm	5	25	230 V	
2450HT012	18 mm	37 mm	7	35	230 V
2453HT012	37 mm	74 mm	3	15	230 V
2451HT012	26 mm	52 mm	5	25	230 V
2454HT012	52 mm	105 mm	1	10	230 V
3450HT012	46 mm	32 mm	1	20	230 V
1100HT012	25 mm	50 mm	5	25	230 V
1101HT012	50 mm	100 mm	5	10	230 V
1110HT012	15 mm	80 mm	5	25	230 V
1111HT012	30 mm	100 mm	2	10	230 V
1112HT012	40 mm	150 mm	2	10	230 V
0400HT013	50 mm	5	25	240 V	
0401HT013	100 mm	1	10	240 V	
2452HT013	32 mm	65 mm	4	20	240 V
0401HT015	100 mm	1	10	400 V	
0402HT015	150 mm	1	5	400 V	
0403HT015	200 mm	1	3	400 V	
0400HT015-BULK	50 mm	25	750	400 V	
0400HT015	50 mm	5	25	400 V	

2452HT015	32 mm 65 mm	4	20	400 V	□
2451HT015	26 mm 52 mm	5	25	400 V	□
2453HT015	37 mm 74 mm	3	15	400 V	□
2455HT015	65 mm 131 mm	1	10	400 V	□
2458HT015	120 mm 200 mm	1	3	400 V	□
2454HT015	52 mm 105 mm	1	10	400 V	□
3451HT015	52 mm 37 mm	3	15	400 V	□
3450HT015	46 mm 32 mm	1	25	400 V	□
3454HT015	105 mm 74 mm	1	10	400 V	□
3455HT015	148 mm 105 mm	1	5	400 V	□
1100HT015	25 mm 50 mm	5	25	400 V	□
1101HT015	50 mm 100 mm	5	10	400 V	□
1110HT015	15 mm 80 mm	5	25	400 V	□
1111HT015	30 mm 100 mm	2	10	400 V	□
1112HT015	40 mm 150 mm	2	10	400 V	□
0400HT016	50 mm	5	25	440 V	□
0401HT016	100 mm	1	10	440 V	□
2454HT016	52 mm 105 mm	1	10	440 V	□
1100HT016	25 mm 50 mm	5	25	440 V	□
0400HT017	50 mm	5	25	500 V	□
0401HT017	100 mm	1	10	500 V	□
0402HT017	150 mm	1	5	500 V	□
2450HT017	18 mm 37 mm	7	35	500 V	□
3455HT017	148 mm 105 mm	1	5	500 V	□
1100HT018	25 mm 50 mm	5	25	600 V	□
2450HT078	18 mm 37 mm	7	35	24 V AC	□
2456HT151-I-GB-F-D	74 mm 148 mm	1	5	ALTA TENSIONE HIGH VOLTAGE HAUTE TENSION STARKSTROM	□

## WS-HTP

Meaning of the symbolElectrical hazard

Geometric shape rectangular with square corners

□

•

Type	Height	Length	Quantity per sheet	Pack qty	
□ 204101HT012	52 mm	26 mm	5	25	□
204101HT012-BULK	52 mm	26 mm	27	810	□
204102HT012	74 mm	37 mm	3	15	□
204102HT012-BULK	74 mm	37 mm	12	1	□
204103HT012	105 mm	52 mm	1	10	□
204103HT012-BULK	105 mm	52 mm	6	300	□
204101HT015	52 mm	26 mm	5	25	□
204101HT015-BULK	52 mm	26 mm	27	810	□
204102HT015	74 mm	37 mm	3	15	□
204102HT015-BULK	74 mm	37 mm	3	1	□
204103HT015	105 mm	52 mm	1	10	□
204103HT015-BULK	105 mm	52 mm	6	300	□
204000	37 mm	18 mm	7	35	□
204000-BULK	37 mm	18 mm	60	1,080	□
204001	52 mm	26 mm	5	25	□
204001-BULK	52 mm	26 mm	27	810	□
204002	74 mm	37 mm	3	15	□
204002-BULK	74 mm	37 mm	12	1,020	□
204003	105 mm	52 mm	1	10	□
204003-BULK	105 mm	52 mm	6	300	□

## WS-BA

Meaning of the symbolBatteries

Geometric shape triangular

•

Type	Length	Quantity per sheet	Pack qty	
200201	25 mm	24	240	□
200202	50 mm	10	50	□
200203	100 mm	2	10	□
200204	150 mm	2	10	□
200205	200 mm	1	5	□
200206	300 mm	1	1	□

2453BA004	74 mm	15	□
2455BA004	131 mm	10	□

### WS-EX

Meaning of the symbol Explosive atmosphere  
Geometric shape triangular

Type	Printed text	Height	Length	Quantity per sheet	Pack qty	
200301			25 mm	24	240	□
200302			50 mm	10	50	□
200303			100 mm	2	10	□
200304			150 mm	2	10	□
200305			200 mm	1	5	□
200306			300 mm	1	1	□

### WS-FM

Meaning of the symbol Flammable materials  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
□ 200801	25 mm	24	240	□
200802	50 mm	10	50	□
200806	300 mm	1	1	□

### WS-CA

Meaning of the symbol Combustible materials  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
200901	25 mm	24	240	□
200902	50 mm	10	50	□
200903	100 mm	2	10	□
200904	150 mm	2	10	□
200905	200 mm	1	5	□
200906	300 mm	1	1	□

### WS-EM

Meaning of the symbol Explosive materials  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
201001	25 mm	24	240	□
201002	50 mm	10	50	□
201003	100 mm	2	10	□
201004	150 mm	2	10	□
201005	200 mm	1	5	□
201006	300 mm	1	1	□

### WS-GT

Meaning of the symbol Pressurised containers or cylinders  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
201102	50 mm	10	50	□
201103	100 mm	2	10	□
201104	150 mm	2	10	□
201105	200 mm	1	5	□
201106	300 mm	1	1	□

## WS-CM

Meaning of the symbol Corrosive substances  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
200501	25 mm	24	240
200502	50 mm	10	50
200503	100 mm	2	10
200504	150 mm	2	10
200505	200 mm	1	5
200506	300 mm	1	1

## WS-HM

Meaning of the symbol Toxic, harmful or irritant substances  
Geometric shape triangular

Type	Length	Pack qty	Quantity per sheet
200600	12.5 mm	320	64
200601	25 mm	240	24
200602	50 mm	50	10
200603	100 mm	10	2
200604	150 mm	10	2
200605	200 mm	5	1
200606	300 mm	1	1

## WS-MF

Meaning of the symbol Magnetic field  
Geometric shape triangular

Type	Printed text	Height	Length	Quantity per sheet	Pack qty
201401			25 mm	24	240
201402			50 mm	10	50
201403			100 mm	2	10
201404			150 mm	2	10
201405			200 mm	1	5
201406			300 mm	1	1

## WS-EF

Meaning of the symbol Non-ionising radiation  
Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
201503	100 mm	2	10
201504	150 mm	2	10
201505	200 mm	1	5
201506	300 mm	1	1
201502	50 mm	10	50

## WS-HN

Meaning of the symbol High noise  
Geometric shape triangular

Type	Printed text	Length	Quantity per sheet	Pack qty
201901		25 mm	24	240
201902		50 mm	10	50
201903		100 mm	2	10
201904		150 mm	2	10
201905		200 mm	1	5

201906

300 mm

1

1

□

## WS-IC

Meaning of the symbol Low temperature

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
201301	25 mm	24	240	□
201302	50 mm	10	50	□
201303	100 mm	2	10	□
201304	150 mm	2	10	□
201305	200 mm	1	5	□

## WS-HS

Meaning of the symbol High temperature

Geometric shape triangular

Type	Length	Height	Quantity per sheet	Printed text	Pack qty	
201200	12.5 mm		64		320	□
201200-BULK	12.5 mm		323		1,615	□
201201	25 mm		24		240	□
201201-BULK	25 mm		120		1,200	□
201202	50 mm		10		50	□
201202-BULK	50 mm		30		900	□
201203	100 mm		2		10	□
201203-BULK	100 mm		6		450	□
201204	150 mm		2		10	□
201205	200 mm		1		5	□
201206	300 mm		1		1	□
0400HS001	50 mm		5	Alta temperatura	25	□
0400HS001-GB	50 mm		5	High temperature	25	□
2453HS001	74 mm	37 mm		Alta temperatura	15	□
2455HS001	131 mm	65 mm		Alta temperatura	10	□
0402HS004-GB	150 mm		1	High temperature zone	5	□
2454HS004-GB	105 mm	52 mm	1	High temperature zone	10	□

## WS-LD

Meaning of the symbol Danger of death

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
200401	25 mm	24	240	□
200402	50 mm	10	50	□
200403	100 mm	2	10	□
200404	150 mm	1	10	□
200405	200 mm	1	5	□
200406	300 mm	1	1	□

## WS-RM

Meaning of the symbol

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
201601	25 mm	24	240	□
201602	50 mm	10	50	□
201603	100 mm	2	10	□
201604	150 mm	1	10	□
201605	200 mm	1	5	□
201606	300 mm	1	1	□

## WS-MS

Meaning of the symbol Moving stairlift

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
201701	25 mm	24	240
201702	50 mm	10	50
201703	100 mm	2	10
201704	150 mm	1	10
201705	200 mm	1	5
201706	300 mm	1	1

## WS-BH

Geometric shape triangular

Meaning of the symbol Biological risk

Type	Length	Quantity per sheet	Pack qty
200701	25 mm	24	240
200702	50 mm	10	50
200703	100 mm	2	10
200704	150 mm	1	10
200705	200 mm	1	5
200706	300 mm	1	1

## WS-WR

Meaning of the symbol UV welding radiation

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
202002	50 mm	10	50
202003	100 mm	2	10
202004	150 mm	1	10
202005	200 mm	1	5
202006	300 mm	1	1

## WS-TC

Meaning of the symbol Splinter ejection

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
202102	50 mm	10	50
202103	100 mm	2	10
202104	150 mm	1	10
202105	200 mm	1	5
202106	300 mm	1	1

## WS-MO

Meaning of the symbol Moving mechanical components

Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
202501	25 mm	24	240
202502	50 mm	10	50
202503	100 mm	2	10
202504	150 mm	2	10
202505	200 mm	1	5
202506	300 mm	1	1



## WS-MM

Geometric shape triangular  
 Meaning of the symbolCutter

Type	Length	Quantity per sheet	Pack qty
202401	25 mm	24	240
202402	50 mm	10	50
202403	100 mm	2	10
202404	150 mm	2	10
202405	200 mm	1	5
202406	300 mm	1	1

## WS-RC

Meaning of the symbolRemote control equipment  
 Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
201801	25 mm	24	240
201802	50 mm	10	50
201803	100 mm	2	10
201804	150 mm	2	10
201805	200 mm	1	5
201806	300 mm	1	1

## WS-WH

Geometric shape triangular  
 Meaning of the symbolIncandescent material splashes

Type	Length	Quantity per sheet	Pack qty
202201	25 mm	24	240
202202	50 mm	10	50
202203	100 mm	2	10
202204	150 mm	2	10
202205	200 mm	1	5
202206	300 mm	1	1

## WS-AS

Geometric shape triangular  
 Meaning of the symbolAutomatic start

Type	Printed text	Height	Length	Quantity per sheet	Pack qty
202302			50 mm	10	50
202303			100 mm	2	10
202304			150 mm	2	10
202305			200 mm	1	5
202306			300 mm	1	1

## WS-FG

Geometric shape triangular  
 Meaning of the symbolFalling materials

Type	Length	Quantity per sheet	Pack qty
202602	50 mm	10	50
202603	100 mm	2	10
202604	150 mm	2	10
202605	200 mm	1	5
202606	300 mm	1	1

## WS-HL

Geometric shape triangular  
 Meaning of the symbol Suspended loads

Type	Printed text	Height	Length	Quantity per sheet	Pack qty
202702			50 mm	10	50
202703			100 mm	2	10
202704			150 mm	2	10
202705			200 mm	1	5
202706			300 mm	1	1

## WS-AF

Geometric shape triangular  
 Meaning of the symbol Hole in the ground

Type	Length	Quantity per sheet	Pack qty
203201	25 mm	24	240
203202	50 mm	10	50
203203	100 mm	2	10
203204	150 mm	2	10
203205	200 mm	1	5
203206	300 mm	1	1

## WS-DF

Geometric shape triangular  
 Meaning of the symbol Danger of falling

Type	Length	Quantity per sheet	Pack qty
203301	25 mm	24	240
203302	50 mm	10	50
203303	100 mm	2	10
203304	150 mm	2	10
203305	200 mm	1	5
203306	300 mm	1	1

## WS-DO

Geometric shape triangular  
 Meaning of the symbol Obstacles on ground

Type	Length	Quantity per sheet	Pack qty
203401	25 mm	24	240
203402	50 mm	10	50
203403	100 mm	2	10
203404	150 mm	2	10
203405	200 mm	1	5
203406	300 mm	1	1

## WS-SD

Geometric shape triangular  
 Meaning of the symbol Slippery surface

Type	Length	Quantity per sheet	Pack qty
203501	25 mm	24	240
203502	50 mm	10	50
203503	100 mm	2	10
203504	150 mm	2	10
203505	200 mm	1	5
203506	300 mm	1	1

## WS-CH

Meaning of the symbol Danger to hands

Geometric shape triangular

Type	Printed text	Height	Length	Quantity per sheet	Pack qty
202800			12.5 mm	64	320
202800-BULK			12.5 mm	323	1,615
202801			25 mm	24	240
202801-BULK			25 mm	120	1,200
202802			50 mm	10	50
202802-BULK			50 mm	30	900
202803			100 mm	2	10
202803-BULK			100 mm	6	450
202804			150 mm	2	10
202805			200 mm	1	5
202806			300 mm	1	1

## WS-MB

Geometric shape triangular

Meaning of the symbol Danger of crushing

Type	Printed text	Height	Length	Quantity per sheet	Pack qty
202902			50 mm	10	50
202903			100 mm	2	10
202904			150 mm	2	10
202905			200 mm	1	5
202906			300 mm	1	1

## WS-PA

Geometric shape triangular

Meaning of the symbol Vehicles crossing

Type	Length	Quantity per sheet	Pack qty
203601	25 mm	24	240
203602	50 mm	10	50
203603	100 mm	2	10
203604	150 mm	2	10
203605	200 mm	1	5
203606	300 mm	1	1

## WS-VR

Geometric shape triangular

Meaning of the symbol Rail vehicles

Type	Length	Quantity per sheet	Pack qty
203701	25 mm	24	240
203702	50 mm	10	50
203703	100 mm	2	10
203704	150 mm	2	10
203705	200 mm	1	5
203706	300 mm	1	1

## WS-MC

Geometric shape triangular

Meaning of the symbol Lift trucks

Type	Length	Quantity per sheet	Pack qty
203102	50 mm	10	50

203103	100 mm	2	10	□
203104	150 mm	2	10	□
203105	200 mm	1	5	□
203106	300 mm	1	1	□

## WS-MT

Geometric shape triangular  
 Meaning of the symbol Danger of tipping

Type	Length	Quantity per sheet	Pack qty	
203002	50 mm	10	50	□
203003	100 mm	2	10	□
203004	150 mm	2	10	□
203005	200 mm	1	5	□
203006	300 mm	1	1	□

## WS-DD

Meaning of the symbol Danger of death  
 Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
204702	50 mm	10	50	□
204703	100 mm	2	10	□
204704	150 mm	2	10	□
204705	200 mm	1	5	□
204706	300 mm	1	1	□

## WS-OL

Geometric shape triangular  
 Meaning of the symbol Ray optics

Type	Length	Quantity per sheet	Pack qty	
204902	50 mm	10	50	
204903	100 mm	2	10	
204904	150 mm	2	10	
204905	200 mm	1	5	
204906	300 mm	1	1	

## WS-ST

Geometric shape triangular  
 Meaning of the symbol water vapor

Type	Length	Quantity per sheet	Pack qty	
204801	25 mm	24	240	□
204802	50 mm	10	50	□
204803	100 mm	2	10	□
204804	150 mm	2	10	□
204805	200 mm	1	5	□
204806	300 mm	1	1	□

## WS-BS

Meaning of the symbol High temperature  
 Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty	
205002	50 mm	10	50	□
205003	100 mm	2	10	□
205004	150 mm	2	10	□

205005	200 mm	1	5	□
205006	300 mm	1	1	□

## WS-HK

Geometric shape triangular  
 Meaning of the symbol Lifting hook

Type	Length	Quantity per sheet	Pack qty	
□ 204602	50 mm	10	50	□
204603	100 mm	2	10	□
204604	150 mm	2	10	□
204605	200 mm	1	5	□

## WS-PR

Geometric shape triangular  
 Meaning of the symbol Automatic carrier

Type	Length	Quantity per sheet	Pack qty	
205102	50 mm	10	50	□
205103	100 mm	2	10	□
205104	150 mm	2	10	□
205105	200 mm	1	5	□
205106	300 mm	1	1	□

## WS-LF

Geometric shape triangular  
 Meaning of the symbol Lifting forks

Type	Length	Quantity per sheet	Pack qty	
204502	50 mm	10	50	□
204503	100 mm	2	10	□
204504	150 mm	2	10	□
204505	200 mm	1	5	□

## WS-WD

Geometric shape triangular  
 Meaning of the symbol Watchdog

Type	Length	Quantity per sheet	Pack qty	
205203	100 mm	2	10	□
205204	150 mm	2	10	□
205205	200 mm	1	5	□
205206	300 mm	1	1	□

## WS-LR

Type	Length	Quantity per sheet	Pack qty	
203801	25 mm	24	240	□
203802	50 mm	10	50	□
203803	100 mm	2	10	□
203804	150 mm	2	10	□
203805	200 mm	1	5	□
203806	300 mm	1	1	□

## WS-LB

Meaning of the symbol Laser  
 Geometric shape triangular

Type	Length	Quantity per sheet	Pack qty
203900	12.5 mm	64	320
203900-BULK	12.5 mm	323	1,615
203901	25 mm	24	240
203901-BULK	25 mm	120	1,200
203902	50 mm	10	50
203902-BULK	50 mm	30	900
203903	100 mm	2	10
203903-BULK	100 mm	6	450
203904	150 mm	2	10
203905	200 mm	1	5

## WST-TSW

Geometric shapetriangular with appendix

Type	Printed text	Meaning of the symbol	Length	Quantity per sheet	Pack qty
0400AD035-GB	DANGER	Generic hazard	50 mm	5	25
0400AD035-E	¡PELIGRO!	Generic hazard	50 mm	5	25
0400AD035-D	GEFAHR	Generic hazard	50 mm	5	25
0400HT008	110 V	Electrical hazard	50 mm	5	25
0400HT008-BULK	110 V	Electrical hazard	50 mm	25	750
0400HT024	Alta tensione	Electrical hazard	50 mm	5	25
0400HT024-GB	High voltage	Electrical hazard	50 mm	5	25
0400HT024-F	Haute tension	Electrical hazard	50 mm	5	25
0400HT024-E	Alta Tensión	Electrical hazard	50 mm	5	25
0400HT056	Scariche elettriche	Electrical hazard	50 mm	5	25
0400HT056-GB	Electrical discharges	Electrical hazard	50 mm	5	25
0400HT056-F	Décharges électriques	Electrical hazard	50 mm	5	25
0400HT056-E	Descargas eléctricas	Electrical hazard	50 mm	5	25
0400HT056-D	Elektrischer Kurzschluss	Electrical hazard	50 mm	5	25
0400HT066	PERICOLO	Electrical hazard	50 mm	5	25
0400HT066-GB	DANGER	Electrical hazard	50 mm	5	25
0400HT066-E	PELIGRO	Electrical hazard	50 mm	5	25
0400HT066-D	GEFAHR	Electrical hazard	50 mm	5	25
0400HS001	Alta temperatura	High temperature	50 mm	5	25
0400HS001-GB	High temperature	High temperature	50 mm	5	25
0400HS001-D	Hochtemperatur	High temperature	50 mm	5	25
0400CH001-GB	Danger to hands	Danger to hands	50 mm	5	25
0400HT075	400 V AC	Electrical hazard	50 mm	5	25
0400HT085	415 V	Electrical hazard	50 mm	5	25
0401HT094	480 V / 24 V	Electrical hazard	100 mm	2	10
0401HT095	400 V / 24 V	Electrical hazard	100 mm	2	10
0401HT098	600 V / 24 V	Electrical hazard	100 mm	2	10
0401HT103	440 V / 24 V	Electrical hazard	100 mm	2	10
0401HT104	230 V / 24 V	Electrical hazard	100 mm	1	10
0401HT105	690 V	Electrical hazard	100 mm	1	10
0400HT113	215 V	Electrical hazard	50 mm	5	25
0400HT122	750 V	Electrical hazard	50 mm	5	25

## WST-LSY

Geometric shaperectangular with square corners

Type	Printed text	Meaning of the symbol	Length	Height	Pack qty
2453BA004	Acidi pericolosi	Batteries	74 mm	37 mm	15
2455BA004	Acidi pericolosi	Batteries	131 mm	65 mm	10
2453HS001	Alta temperatura	High temperature	74 mm	37 mm	15
2455HS001	Alta temperatura	High temperature	131 mm	65 mm	10
2453BA004-GB	Dangerous acids	Batteries	74 mm	37 mm	15
2453BA004-F	Acides dangereux	Batteries	74 mm	37 mm	15
2453BA004-E	Ácidos peligrosos	Batteries	74 mm	37 mm	15
2453BA004-D	Gefährliche Säuren	Batteries	74 mm	37 mm	15
2455BA004-GB	Dangerous acids	Batteries	131 mm	65 mm	10
2455BA004-F	Acides dangereux	Batteries	131 mm	65 mm	10
2455BA004-E	Ácidos peligrosos	Batteries	131 mm	65 mm	10

2455BA004-D	Gefährliche Säuren	Batteries	131 mm	65 mm	10	□
2453EX001-GB	Explosive atmosphere	Explosive atmosphere	74 mm	37 mm	15	□
2453EX001-F	Atmosphère explosive	Explosive atmosphere	74 mm	37 mm	15	□
2453EX001-E	Atmósfera explosiva	Explosive atmosphere	74 mm	37 mm	15	□
2453EX001-D	Explosionsfähige Atmosphäre	Explosive atmosphere	74 mm	37 mm	15	□
2455EX001-GB	Explosive atmosphere	Explosive atmosphere	131 mm	65 mm	10	□
2455EX001-F	Atmosphère explosive	Explosive atmosphere	131 mm	65 mm	10	□
2455HS001-GB	High temperature	High temperature	131 mm	65 mm	10	□
2453HS001-GB	High temperature	High temperature	74 mm	37 mm	15	□
2455EX001-D	Explosionsfähige Atmosphäre	Explosive atmosphere	131 mm	65 mm	10	□
2455EX001-E	Atmósfera explosiva	Explosive atmosphere	131 mm	65 mm	10	□

## WST-LAY

Geometric shaperectangular with square corners

Type	Printed text	Meaning of the symbol	Length	Height	Quantity per sheet	Pack qty
2653AD035	ATTENZIONE! PERICOLO	Generic hazard	74 mm	37 mm	3	15 □
2653AD035-GB	WARNING! DANGER	Generic hazard	74 mm	37 mm	3	15 □
2653AD035-F	ATTENTION! DANGER	Generic hazard	74 mm	37 mm	3	15 □
2653AD035-E	¡CUIDAD! PELIGRO	Generic hazard	74 mm	37 mm	3	15 □
2653AD035-D	ACHTUNG! GEFAHR	Generic hazard	74 mm	37 mm	3	15 □
2655AD035-GB	WARNING! DANGER	Generic hazard	131 mm	65 mm	1	10 □
2655AD035-F	ATTENTION! DANGER	Generic hazard	131 mm	65 mm	1	10 □
2655AD035-E	¡CUIDAD! PELIGRO	Generic hazard	131 mm	65 mm	1	10 □
2655AD035-D	ACHTUNG! GEFAHR	Generic hazard	131 mm	65 mm	1	10 □
2653HT024	ATTENZIONE! Alta tensione	Electrical hazard	74 mm	37 mm	3	15 □
2653HT024-GB	WARNING! High voltage	Electrical hazard	74 mm	37 mm	3	15 □
2653HT024-F	ATTENTION! Haute tension	Electrical hazard	74 mm	37 mm	3	15 □
2653HT024-E	¡ATENCIÓN! Alta tensión	Electrical hazard	74 mm	37 mm	3	15 □
2653HT024-D	ACHTUNG! Hochspannung	Electrical hazard	74 mm	37 mm	3	15 □
2655HT024	ATTENZIONE! Alta tensione	Electrical hazard	131 mm	65 mm	1	10 □
2655HT024-GB	WARNING! High voltage	Electrical hazard	131 mm	65 mm	1	10 □
2655HT024-F	ATTENTION! Haute tension	Electrical hazard	131 mm	65 mm	1	10 □
2655HT024-E	¡ATENCIÓN! Alta tensión	Electrical hazard	131 mm	65 mm	1	10 □
2655HT024-D	ACHTUNG! Hochspannung	Electrical hazard	131 mm	65 mm	1	10 □
2653HT039	ATTENZIONE! Apparecchiatura sempre sotto tensione, anche ad interruttore aperto	Electrical hazard	74 mm	37 mm	3	15 □
2653HT039-GB	WARNING! Equipment remains live even when switched off	Electrical hazard	74 mm	37 mm	3	15 □
2653HT039-F	ATTENTION! Appareillage toujours sous tension, même avec interrupteur ouvert	Electrical hazard	74 mm	37 mm	3	15 □
2653HT039-E	¡ATENCIÓN! Equipo siempre bajo tensión, incluso cuando el interruptor está abierto	Electrical hazard	74 mm	37 mm	3	15 □
2653HT039-D	ACHTUNG! Einrichtung immer unter Spannung, auch mit offenen Schalter	Electrical hazard	74 mm	37 mm	3	15 □
2655HT039	ATTENZIONE! Apparecchiatura sempre sotto tensione, anche ad interruttore aperto	Electrical hazard	131 mm	65 mm	1	10 □
2655HT039-GB	WARNING! Equipment remains live even when switched off	Electrical hazard	131 mm	65 mm	1	10 □
2655HT039-E	¡ATENCIÓN! Equipo siempre bajo tensión, incluso cuando el interruptor está abierto	Electrical hazard	131 mm	65 mm	1	10 □
2655HT039-D	ACHTUNG! Einrichtung immer unter Spannung, auch mit offenen Schalter	Electrical hazard	131 mm	65 mm	1	10 □
2653HT051	ATTENZIONE! Tensione sempre presente	Electrical hazard	74 mm	37 mm	3	15 □
2653HT051-GB	WARNING! Always live	Electrical hazard	74 mm	37 mm	3	15 □
2653HT051-F	ATTENTION! Tension toujours présente	Electrical hazard	74 mm	37 mm	3	15 □
2653HT051-E	¡ATENCIÓN! Presencia de tensión	Electrical hazard	74 mm	37 mm	3	15 □
2653HT051-D	ACHTUNG! Spannung ständig vorhanden	Electrical hazard	74 mm	37 mm	3	15 □
2655HT051	ATTENZIONE! Tensione sempre presente	Electrical hazard	131 mm	65 mm	1	10 □

2655HT051-GB	WARNING! Always live	Electrical hazard	131 mm	65 mm 1	10	□
2655HT051-F	ATTENTION! Tension toujours présente	Electrical hazard	131 mm	65 mm 1	10	□
2655HT051-E	¡ATENCIÓN! Presencia de tensión	Electrical hazard	131 mm	65 mm 1	10	□
2655HT051-D	ACHTUNG! Spannung ständig vorhanden	Electrical hazard	131 mm	65 mm 1	10	□
2653HT052	ATTENZIONE! Togliere tensione prima di aprire lo sportello	Electrical hazard	74 mm	37 mm 3	15	□
2653HT052-GB	WARNING! Switch power off before opening the door	Electrical hazard	74 mm	37 mm 3	15	□
2653HT052-F	ATTENTION! Mettre hors tension avant d'ouvrir le panneau	Electrical hazard	74 mm	37 mm 3	15	□
2653HT052-E	¡ATENCIÓN! Desconectar la tensión antes de abrir la puerta	Electrical hazard	74 mm	37 mm 3	15	□
2653HT052-D	ACHTUNG! Die Spannung vor Öffnen der Tür ausschalten	Electrical hazard	74 mm	37 mm 3	15	□
2653HT052-BULK	ATTENZIONE! Togliere tensione prima di aprire lo sportello	Electrical hazard	74 mm	37 mm 34	1,020	□
2653HT052-GB-BULK	WARNING! Switch power off before opening the door	Electrical hazard	74 mm	37 mm 34	1,020	□
2653HT052-F-BULK	ATTENTION! Mettre hors tension avant d'ouvrir le panneau	Electrical hazard	74 mm	37 mm 34	1,020	□
2653HT052-D-BULK	ACHTUNG! Die Spannung vor Öffnen der Tür ausschalten	Electrical hazard	74 mm	37 mm 34	1,020	□
2655HT052	ATTENZIONE! Togliere tensione prima di aprire lo sportello	Electrical hazard	131 mm	65 mm 1	10	□
2655HT052-GB	WARNING! Switch power off before opening the door	Electrical hazard	131 mm	65 mm 1	10	□
2655HT052-F	ATTENTION! Mettre hors tension avant d'ouvrir le panneau	Electrical hazard	131 mm	65 mm 1	10	□
2655HT052-E	¡ATENCIÓN! Desconectar la tensión antes de abrir la puerta	Electrical hazard	131 mm	65 mm 1	10	□
2655HT052-D	ACHTUNG! Die Spannung vor Öffnen der Tür ausschalten	Electrical hazard	131 mm	65 mm 1	10	□
2653HT056	ATTENZIONE! Scariche elettriche	Electrical hazard	74 mm	37 mm 3	15	□
2653HT056-GB	WARNING! Electrical discharges	Electrical hazard	74 mm	37 mm 3	15	□
2653HT056-F	ATTENTION! Décharges électriques	Electrical hazard	74 mm	37 mm 3	15	□
2653HT056-E	¡ATENCIÓN! Descargas eléctricas	Electrical hazard	74 mm	37 mm 3	15	□
2653HT056-D	ACHTUNG! Elektrischer Kurzschluss	Electrical hazard	74 mm	37 mm 3	15	□
2655HT056	ATTENZIONE! Scariche elettriche	Electrical hazard	131 mm	65 mm 1	10	□
2655HT056-GB	WARNING! Electrical discharges	Electrical hazard	131 mm	65 mm 1	10	□
2655HT056-F	ATTENTION! Décharges électriques	Electrical hazard	131 mm	65 mm 1	10	□
2655HT056-E	¡ATENCIÓN! Descargas eléctricas	Electrical hazard	131 mm	65 mm 1	10	□
2655HT056-D	ACHTUNG! Elektrischer Kurzschluss	Electrical hazard	131 mm	65 mm 1	10	□
2653HT061	ATTENZIONE! Apparechiatura sotto tensione, anche a sportello aperto	Electrical hazard	74 mm	37 mm 3	15	□
2653HT061-GB	WARNING! Equipment remains live even when door is open	Electrical hazard	74 mm	37 mm 3	15	□
2653HT061-F	ATTENTION! Equipement sous tension même lorsque le panneau est ouvert	Electrical hazard	74 mm	37 mm 3	15	□
2653HT061-E	¡ATENCIÓN! Maquinaria bajo tensión incluso con la puerta abierta	Electrical hazard	74 mm	37 mm 3	15	□
2653HT061-D	ACHTUNG! Vorrichtung auch bei geöffneter Tür unter Spannung	Electrical hazard	74 mm	37 mm 3	15	□
2655HT061	ATTENZIONE! Apparechiatura sotto tensione, anche a sportello aperto	Electrical hazard	131 mm	65 mm 1	10	□
2655HT061-GB	WARNING! Equipment remains live even when door is open	Electrical hazard	131 mm	65 mm 1	10	□
2655HT061-F	ATTENTION! Equipement sous tension même lorsque le panneau est ouvert	Electrical hazard	131 mm	65 mm 1	10	□
2655HT061-E	¡ATENCIÓN! Maquinaria bajo tensión incluso con la puerta abierta	Electrical hazard	131 mm	65 mm 1	10	□
2655HT061-D	ACHTUNG! Vorrichtung auch bei geöffneter Tür unter Spannung	Electrical hazard	131 mm	65 mm 1	10	□
2653HT072	ATTENZIONE! Togliere tensione prima di rimuovere il coperchio	Electrical hazard	74 mm	37 mm 3	15	□
2653HT072-GB	WARNING! Switch off power before removing cover	Electrical hazard	74 mm	37 mm 3	15	□
2653HT072-F	ATTENTION! Mettre hors tension avant d'ouvrir	Electrical hazard	74 mm	37 mm 3	15	□
2653HT072-E	¡ATENCIÓN! Desconectar antes de abrir	Electrical hazard	74 mm	37 mm 3	15	□
2653HT072-D	ACHTUNG! Bevor Deckel öffnen Spannung lösen	Electrical hazard	74 mm	37 mm 3	15	□
2655HT072	ATTENZIONE! Togliere tensione prima di rimuovere il coperchio	Electrical hazard	131 mm	65 mm 1	10	□
2655HT072-GB	WARNING! Switch off power before removing cover	Electrical hazard	131 mm	65 mm 1	10	□



2655HT072-F	ATTENTION! Mettre hors tension avant d'ouvrir	Electrical hazard	131 mm	65 mm	1	10	□
2655HT072-E	¡ATENCIÓN! Desconectar antes de abrir	Electrical hazard	131 mm	65 mm	1	10	□
2655HT072-D	ACHTUNG! Bevor Deckel öffnen Spannung lösen	Electrical hazard	131 mm	65 mm	1	10	□
2653HT081	ATTENZIONE! Togliere tensione prima di rimuovere la protezione	Electrical hazard	74 mm	37 mm	3	15	□
2653HT081-GB	WARNING! Switch off power before removing the guard	Electrical hazard	74 mm	37 mm	3	15	□
2653HT081-F	ATTENTION! Mettre hors tension avant de retirer la protection	Electrical hazard	74 mm	37 mm	3	15	□
2653HT081-E	¡ATENCIÓN! Desconectar la tensión antes de quitar la protección	Electrical hazard	74 mm	37 mm	3	15	□
2653HT081-D	ACHTUNG! Bevor Schutz öffnen Spannung lösen	Electrical hazard	74 mm	37 mm	3	15	□
2655HT081	ATTENZIONE! Togliere tensione prima di rimuovere la protezione	Electrical hazard	131 mm	65 mm	1	10	□
2655HT081-GB	WARNING! Switch off power before removing the guard	Electrical hazard	131 mm	65 mm	1	10	□
2655HT081-F	ATTENTION! Mettre hors tension avant de retirer la protection	Electrical hazard	131 mm	65 mm	1	10	□
2655HT081-E	¡ATENCIÓN! Desconectar la tensión antes de quitar la protección	Electrical hazard	131 mm	65 mm	1	10	□
2655HT081-D	ACHTUNG! Bevor Schutz öffnen Spannung lösen	Electrical hazard	131 mm	65 mm	1	10	□
2652HT123	ATTENZIONE! Impianto fotovoltaico in azione durante le ore diurne - 400 V	Electrical hazard	65 mm	32 mm	4	20	□
2652HT124	ATTENZIONE! Impianto fotovoltaico in azione durante le ore diurne - 600 V	Electrical hazard	65 mm	32 mm	4	20	□
2652HT125	ATTENZIONE! Impianto fotovoltaico in azione durante le ore diurne - 800 V	Electrical hazard	65 mm	32 mm	4	20	□
2652-HT126-E	¡Atención! Instalación fotovoltaica en funcionamiento durante las horas diurnas	Electrical hazard	65 mm	32 mm	4	20	□

## WST-OTY

Geometric shaperectangular with rounded corners

Type	Printed text	Length	Height	Quantity per sheet	Pack qty
1114PV003R-F	COUPURE D'URGENCE ENTREE ONDULEUR	40 mm	20 mm	25	25 □
1114PV002R-F	COUPURE D'URGENCE SORTIE ONDULEUR	40 mm	20 mm	25	25 □
1114PV001R-F	SECTIONNEMENT GÉNÉRAL INSTALLATION PHOTOVOLTAÏQUE	40 mm	20 mm	25	25 □
1114PV003R	ARRESTO D'EMERGENZA ENTRATA INVERTER	40 mm	20 mm	25	25 □
1114PV002R	ARRESTO D'EMERGENZA USCITA INVERTER	40 mm	20 mm	25	25 □
1114PV001R	SEZIONAMENTO GENERALE INSTALLAZIONE FOTOVOLTAICA	40 mm	20 mm	25	25 □

## WST-PSY

Geometric shaperectangular with rounded corners

Type	Printed text	Meaning of the symbol
3460PV013-GB	PV ARRAY MODULE DANGER contains live parts during daylight	Electrical hazard □
3460PV012-GB	PV ARRAY DC ISOLATOR DANGER contains live parts during daylight	Electrical hazard □
3460HT131-GB	DC CABLE DANGER High Voltage	Electrical hazard □
3460HT130-GB	DO NOT disconnect DC plugs and sockets under load Turn off AC supply first	Electrical hazard □
3460PV011-GB	PV SYSTEM Main AC isolator	Electrical hazard □
3460PV010-GB	PV ARRAY DC JUNCTION BOX DANGER contains live parts during daylight	Electrical hazard □
3460HT129-GB	INVERTER Isolate AC and DC before carrying out work	Electrical hazard □
3460PV009-GB	PV ARRAY MODULE DANGER contains live parts during daylight	Electrical hazard □

## WST-PAWY

Geometric shaperectangular with rounded corners

Type	Printed text	Meaning of the symbol	Length	Height	Quantity per sheet	Pack qty
3960PV004-F	ATTENTION: Câbles courant continu sous tension		40 mm	50 mm	3	15 □
3960PV004	ATTENZIONE: Cavi e corrente continua sotto tensione		40 mm	50 mm	3	15 □
3960-PV004-E	PRECAUCIÓN: cables de alimentación de CC		40 mm	50 mm	3	15 □

## WST-PSWY

Geometric shaperectangular with rounded corners

Type	Printed text	Meaning of the symbol	Length	Height	Quantity per sheet	Pack qty
3760HT127	Non manovrare sotto carico	Electrical hazard	40 mm	50 mm	3	15 □
3760HT127-F	Ne pas manoeuvrer en charge	Electrical hazard	40 mm	50 mm	3	15 □
3760HT127-E	No utilice más de	Electrical hazard	40 mm	50 mm	3	15 □

## WST-PSWR

Geometric shaperectangular with rounded corners

Type	Meaning of the symbol	Printed text	Length	Height	Quantity per sheet	Pack qty
3760PV006W-F		Coupure réseau de Distribution et Photovoltaïque	40 mm	50 mm	3	15 □
3760PV005W-F		Coupure Photovoltaïque	40 mm	50 mm	3	15 □
3760PV006W		Arresto di rete di distribuzione fotovoltaica	40 mm	50 mm	3	15 □
3760PV005W		Arresto fotovoltaico	40 mm	50 mm	3	15 □

## WST-PSWYR

Geometric shaperectangular with rounded corners

Type	Printed text	Meaning of the symbol	Height	Length	Quantity per sheet	Pack qty
3760PV007BW	Produzione fotovoltaica Arresto di rete di distribuzione		50 mm	40 mm	3	15 □
3760PV007BW-F	Production Photovoltaïque Coupure réseau de Distribution		50 mm	40 mm	3	15 □

## WSE

Geometric shape circular crown

Quantity per sheet1

Type	Printed text	Diameter	Pack qty
204500-GB	Emergency stop	60 mm	10 □
204501-GB	Emergency stop	80 mm	10 □
204500VR-GB	Emergency stop	60 mm	100 □